

InflatorShield™ – High Pressure Pump – 1000 / 2000W



FP 5048 | 230V 50Hz

- 1** High impact ABS enclosure, built to withstand the rigours of industrial use.
- 2** Dual wattage pump designed for use with larger sealed inflatables, rated at 1000W Standard and 2000W with Booster.
- 3** Fitted with IP44 rated C-Form plug as standard suitable for outdoor use.
- 4** The FP5048 is fitted with a high-quality air flow pipe, designed to prevent heat build-up and allow the sealed inflatable to be inflated quickly and efficiently.
- 5** Fitted with a bayonet attachment to fit standard high pressure sealed inflatables.
- 6** Fitted with a thermal overload device to prevent overheating and to protect your pump from damage.

Features and Specification: High pressure pump for rapid inflation and deflation.

Power Supply	230V/50Hz	
Weight	4.10 Kg	
Dimensions	L325mm Ø177mm H265 mm	
Maximum Power	Main Motor (Orange Switch) 1000W	Booster (Orange + Red Switch) 2000W
Maximum Pressure	14KPa/140mbar/2.0psi	35KPa/350mbar/5.0psi
Maximum Flow Rate	1200 l/min	2000 l/min

This high-pressure pump is fitted with a thermal overload device which will operate in case of overheating. Should the thermal overload device operate the high-pressure pump will stop functioning and will operate normally again once it has cooled down after approximately 20-40 minutes.